



FEATURES

- DSP Technology with adjustable filtering
- Future-proof design, modernize in place
- Excellent Repeatability ($\pm 0.05\%$), Accuracy ($\pm 0.1\%$)
- Advanced diagnostics, data processing, logging

BENEFITS

- ▶ Reliable measurement under challenging conditions
- ▶ Safe investment with lower lifecycle costs
- ▶ Increased product quality
- ▶ Optimize control and lifecycle management

SPECIFICATIONS

Display:	240 x 160 pixels
Supply Voltage:	20 ... 27 V DC $\pm 10\%$ 100 ... 240 V AC $\pm 10\%$
Power Consumption:	7.5 W/15 VA
Interfaces:	[CH1]: HART 7.2 or Profibus PA/DP or Modbus RTU [CH2, CH3, CH4]: Plug-In I/O Card
Housing Material:	Aluminum
Protection Class:	IP67/NEMA 4X to IEC 529 and DIN 40050 (1 mH ₂ O for 30 min.)

PLUG-IN I/O-CARD

Available Cards:	Optional, three configurable channels Option 1: Signal I/O, Signal I/O, Signal I/O Option 2: Signal I/O, Signal I/O, Relay
Signal I/O:	Configurable universal I/O channels: current output, digital output or digital input
Current Output:	0 ... 20 mA or 4 ... 20 mA (CH1 only 4 ... 20 mA)
Digital Output:	Pulse: 41.6 μ s ... 5 s pulse duration Frequency: 0 ... 10 kHz Active: 0 ... 24V DC, 110 mA
Digital Input:	15 ... 30 V DC, 2 ... 15 mA
Relay:	Voltage-free contact 30 V AC, 100 mA
Output Value (programmable):	Mass flow, volume flow, total mass, total volume, corrected volume, density, temperature, fraction (flow/mass/%)

TEMPERATURE

Ambient Temp. Transmitter:	-40 °C ... +60 °C [-40 °F ... +140 °F] (humidity max. 95 %)
Ambient Temp. Display:	-20 °C ... +60 °C [-4 °F ... +140 °F]
Storage and Transport:	-20 °C ... +70 °C [-4 °F ... +158 °F]

CONNECTIVITY


Cable:	Standard industrial signal cable up to 200 m long, 2x screened pairs or 4-wire overall
Cable Gland:	½" NPT M20 (on request)



Compact Version



Remote Version (wall mount)



METER DIMENSIONS AND WEIGHTS

A) Meter-Mount Electronics

Weight: 4.5 kg [9.9 lb]

B) Wall-Mount Electronics

Weight: 5.6 kg [12.3 lb] with 3 meter cable

APPROVALS & CERTIFICATIONS

Hazardous area (Ex)

ATEX (Ex)	Zone 1: Group IIC or IIB, T2...T6
ATEX (Exn)	Zone 2: II 3G Ex nA IIC T2...T6 Gc
IECEX (Ex)	Zone 1: Group IIC or IIB, T2...T6
cCSAus (Ex1)	Class 1, Division 1: Group A, B, C, D or C, D, T2...T6

¹⁾ Release pending.

EMC

EN 55011/CISPR-11 (Class A)

EN/IEC 61236-1 (Industry)

N & S AMERICA

AW-Lake Company
2440 W. Corporate Preserve Dr. #600
Oak Creek WI 53154 | USA
+1 414 574 4300

ASIA PACIFIC & MIDDLE EAST

KEM Instruments SEA Pte. Ltd.
UEN: 2017177922
1003 Bukit Merah Central #06-32
Singapore 159836
+65 6274 1130

CHINA

KEM flow technology (Beijing) Co., Ltd.
Rm. 906, Block C, Ruiipu Office Bldg, No. 15
HongJunYingNan Road
Chaoyang District, Beijing 100012 | China
+86 10 84929567

REST OF WORLD

KEM Küppers Elektromechanik GmbH
Liebigstraße 5
85757 Karlsfeld | Germany
+49 8131 59391-100